UNCLASSIFIED

AD NUMBER AD038070 CLASSIFICATION CHANGES TO: unclassified FROM: confidential LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to DoD only; Administrative/Operational Use; 31 MAY 1964. Other requests shall be referred to Bureau of Ships, Washington, DC.

AUTHORITY

31 May 1966, DoDD 5200.10; BUSHIPS ltr, 1 Apr 1968

UNCLASSIFIED

AD NUMBER AD038070 CLASSIFICATION CHANGES TO: unclassified FROM: confidential LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to DoD and DoD contractors only; Administrative/Operational Use; 31 MAY 1954. Other requests shall be referred to Bureau of Ships, Washington, DC.

AUTHORITY

31 May 1966, DoDD 5200.10; BUSHIPS ltr, 1 Apr 1968

Armed Services Technical Information Agency

Because of our limited supply, you are requested to return this copy WHEN IT HAS SERVED YOUR PURPOSE so that it may be made available to other requesters. Your cooperation will be appreciated.

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

Reproduced by DOCUMENT SERVICE CENTER KNOTT BUILDING, DAYTON, 2, 0 HIO

TOTAL WINDS

CONFIDENTIAL



CONFIDENTIAL

54AA 9542

NOTICE: THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 and 794. THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.



CONFIDENTIAL

Copy No. 23

FURTHER DISSEMINATION IS AUTHORIZED ONLY TO MILITARY AGENCIES.

> V-39, V-40 KLYSTRON OSCILLATORS DESIGN AND DEVELOPMENT PROGRAM

Progress Report for Quarter Ending 31 May 1954

Prepared for: Bureau of Ships

Navy Department

On: BuShips Contract No. NObsr-52105

Index No. NE_112044

By: Robert G. Rockwell

Approved:

Sigurd F. Varian

Vice-President for Engineering

7060511-54

54 A A

4954**2**

1



CONFIDENTIAL

PURPOSE

The purpose of the program covered by BuShips Contract No. NObsr-52105 is to design and develop two wide-range klystron oscillators, V-39 and V-40, which will comply with the specifications outlined in this contract.

The two oscillators will cover the frequency band from 10 to 21 kmc. One tube will tune over the lower half of the band from 10 to 15.5 kmc, and the other will cover the band from 15 to 21 kmc. Preliminary design tubes of each type, complete with electrical test and characteristic data, will be furnished. In addition, five tubes embodying the final design of each type will be supplied, along with electrical characteristics and test data, final proposed specifications, and manufacturing drawings.

GENERAL FACTUAL DATA

During this quarter, a mode suppressor design which successfully eliminates the mode interference in the V-39 was perfected. Five V-39's, operating in external cavities incorporating this design, were inspected and accepted by the local Inspector of Naval Material, making a total of nine accepted tubes.

In the V-40 development, a cylindrical choke short for rectangular waveguide was designed and the holes occurring due to the mode suppressor were eliminated. One tube of the final V-40 design was inspected and accepted, thereby providing six accepted tubes.

DETAILED FACTUAL DATA

The first work attempted in this quarter was to eliminate the interfering modes of the V-39 by means of a mode suppressor placed alongside the main tuning cavity. There were 15 variations of mode suppressor tried

Page 2 of 4



CONFIDENTIAL

before a design was found which eliminated all detectable interference. This design consisted of a new size and location of the coupling hole to eliminate the $3/2 \lambda$ -mode interference in conjunction with a mode suppressor narrow enough to prevent the λ -mode from being suppressed, and a second, even narrower mode suppressor attached to the opposite side wall with a considerably shorter coupling hole which suppressed the $5/2 \lambda$ -mode interference. A third suppressor was no longer found necessary, but mode-suppressing screw holes have been provided to eliminate some high-frequency modes which appear at the highest beam voltages allowed.

During this quarter, there were five V-39 tubes inspected and accepted by the local Inspector of Naval Material: tubes No. 54, 62, 64, 65, and 66. It was found in these tubes that for a beam voltage as low as about 500 volts, a power output of 50 mw over the tuning range could still be obtained. Consequently, the tubes have been tested with either 500 or 550 volts on the beam.

Delivery of five V-39 tubes will complete the requirements for V-39's on this contract.

In the V-40 development, efforts were concentrated on the design of a cylindrical choke in rectangular waveguide and on elimination of the holes occurring due to the mode suppressor. A V-40 using the cylindrical choke short was tested and found to oscillate from about 21.5 or 22 kmc down to 14.3 kmc.

V-40 tube No. 67 was inspected and accepted by the local Inspector of Naval Material. Manufacturing drawings which will be included in the final report will be of V-40 No. 67, which uniquely includes the cylindrical choke short in the tuning cavity.

V-40 tube No. 54, accepted previously, and tube No. 67 were then re-examined, and it was found that the power output drops below 50 mw when the beam voltage is lowered. The tubes easily attain a power output of over 20 mw at a beam voltage of 650 volts, however.

Page 3 of 4



CONFIDENTIAL

A total of six V-40 tubes of the final design (tubes No. 54, 58, 59, 62, 65, and 67) have now been inspected and accepted. Tube No. 58 was shipped in June 1953, and tubes No. 59 and 62 were shipped in December 1953. Delivery of two of the three remaining accepted V-40 tubes will complete the requirements for V-40's on this contract.

A final report of the complete work covered by this program is now in preparation. Delivery of the final report will complete this contract.

CONCLUSIONS

Tubes of the V-39 and V-40 types have now been successfully developed, culminating the work of several months. Delivery of five tubes of each type which will complete the tube requirements on this contract, will take place upon receipt of shipping instructions. A final report covering the work in this program is now being prepared, and submission of this report will complete the contract.

Estimated expenditures during May 1954: \$2,364.00 Estimated man-hours during May 1954: 251

Page 4 of 4

Armed Services Technical Information Agency

Because of our limited supply, you are requested to return this copy WHEN IT HAS SERVED YOUR PURPOSE so that it may be made available to other requesters. Your cooperation will be appreciated.

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

Reproduced by DOCUMENT SERVICE CENTER KNOTT BUILDING, DAYTON, 2, 0HIO